

AUM 022 N.1 - automatic washbasin w/out sheathing with connection to one water - 12 V, 50 Hz



AUM 022 is a small stainless steel washbasin intended to be mounted on the wall. Due to its small size, this washbasin is suitable especially for areas with less space where the requirements for hygiene are required. The washbasin is produced in two standard version types: with fixing consoles (AUM 022N) and more durable version with stainless sheathing (AUM 022Z). Surface finish is standardly brushed, but sandblasted matt finish is possible on order. The washbasin can be delivered either without an automatic tap, only with opening of diameter of 29 mm for the tap or fitted with our popular automatic tap AUM 3 in all version types - for one water, for hot and cold water or with thermostatic valve. All version types can be supplied with 12 V, 50 Hz (from source ZAC) or with 6 V (from AA batteries). The washbasin is manufactured from the stainless steel AISI 304. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 8931211).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUM 022 is a small stainless steel washbasin intended to be mounted on the wall. Due to its small size, this washbasin is suitable especially for areas with less space where the requirements for hygiene are required. The washbasin is produced in two standard version types: with fixing consoles (AUM 022N) and more durable version with stainless sheathing (AUM 022Z). Surface finish is standardly brushed, but sandblasted matt finish is possible on order. The washbasin can be delivered either without an automatic tap, only with opening of diameter of 29 mm for the tap or fitted with our popular automatic tap AUM 3 in all version types - for one water, for hot and cold water or with thermostatic valve. All version types can be supplied with 12 V, 50 Hz (from source ZAC) or with 6 V (from AA batteries). The washbasin is manufactured from the stainless steel AISI 304. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 8931211).

Complete delivery

1. stainless washbasin with consoles (AUM 022 N)
2. stainless washbasin with sheathing (AUM 022 Z)
3. waste trap
4. small anchoring material
5. automatic tap (only with version with automatic tap)

Requirements for setting up the construction

1. Set-up water inlet G 1/2"
2. Set-up electric cable for 12 V from source ZAC (only by 12 V version)
3. Set-up outlet d = 40 mm

Download information about the product

- [AUM 022 N \(všechny verze\) data for projectants - \(30 kB \)](#)
- [AUM 022 Z \(všechny verze\) data for projectants - \(29 kB \)](#)

Basic technical information	Radius of sensor	adjusted automatically
	Water inlet	G 1/2"
	Outlet	d = 40 mm
	Dimensions	400 x 295 x 180 mm AUM 022N
		2 - 8 Bar (by 6 V version)
	Inner dimensions of sink	346 x 248 x 103 mm
	Adjustable time of after flow	0÷4 s (adjusted to 1 sec)
	IP protection	IP 55
	Power supply	12 V, 50 Hz (AUM 022 N.1, .2. TV; AUM 022 Z.1, .2, .TV)
	Source of power supply	ZAC 1/20 - max. 3x AUM 022 N.1, Z.1 N.TV, Z.TV; max. 2x AUM 022 N.2, Z.2)
	Water pressure	1 - 10 Bar (by 12 V version)
	Weight	4 kg

Figures