

AUM 023 - stainless washbasin with waste siphon, without tap



AUM 023 is a stainless steel washbasin, which can be used as more durable and hygienic substitution of standard ceramic washbasin. It is intended to be mounted on the wall. Complete delivery includes waste trap and all anchoring material. Round inner sink gives an interesting design to this washbasin. Standard version does not include the opening for the tap. Opening can be made free of charge. Its diameter and location must be specify with the order. The washbasin can be fitted with the automatic tap AUM 3 in all version types - connected to one water, to hot and cold water or with thermostatic valve, supplied with 12 V from power supply ZAC or with 6 V from AA batteries. After consultation it is also possible to fit the washbasin with other automatic tap from our production range. Standard version has a satin surface finish (sandblasted matt finish is possible on order). The washbasin is manufactured from the stainless steel AISI 304. For cleaning we recommned WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 8931211).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUM 023 is a stainless steel washbasin, which can be used as more durable and hygienic substitution of standard ceramic washbasin. It is intended to be mounted on the wall. Complete delivery includes waste trap and all anchoring material. Round inner sink gives an interesting design to this washbasin. Standard version does not include the opening for the tap. Opening can be made free of charge. Its diameter and location must be specify with the order. The washbasin can be fitted with the automatic tap AUM 3 in all version types - connected to one water, to hot and cold water or with thermostatic valve, supplied with 12 V from power supply ZAC or with 6 V from AA batteries. After consultation it is also possible to fit the washbasin with other automatic tap from our production range. Standard version has a satin surface finish (sandblasted matt finish is possible on order). The washbasin is manufactured from the stainless steel AISI 304. For cleaning we recommned WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 8931211). Complete delivery

1. stainless washbasin
2. small anchoring material
3. waste trap

Requirements for setting up the construction

1. Set-up outlet d = 40 mm according to the scheme
2. Water inlet G 1/2" (only for versions with automatic tap)
3. Power supply 12 V, 50 Hz from source ZAC (only for versions with automatic tap)

Download information about the product

- [AUM 023 data for projectants - \(28 kB \)](#)

Basic technical informationAUM 023

Dimensions	400 x 400 x 181 mm
Inner dimensions of sink	d 327 x 122 mm
Outlet	d = 40 mm
AUM 023.1, .2, .TV (+ battery version .B)	

Water inlet	G 1/2"
Water pressure	1 - 10 Bar (12 V version), 2 - 8 Bar (6 V version)
Power supply	12 V, 50 Hz (AUM 023.1, 023.2, 023.TV)
	ZAC 1/50 - max. 8x AUM 023.1, 023.TV, max. 5x AUM 023.2
Power requirement for 12 V versions	6 VA, (10 VA by AUM 023.2)
Source of power supply for 12 V versions	ZAC 1/20 - max. 3x AUM 023.1, 023.TV, max. 2x AUM 023.2

Figures

