

## AUZ 06 - stainless steel free-standing closet



AUZ 06 is a stainless toilet intended for free-standing on the floor, including grey seat made of hardened durable plastic (white or black seat are possible on order). It is suitable for all places where it is not possible to use wall-hung toilet (e.g. in case of low carrying capacity of the wall). In standard version the outlet is directed into the wall. Outlet directed into the floor is possible on customer's wish. A set with an AUZ 3 automatic flushing system or AUZ 5 automatic flushing system including flushing cistern can be completed. AUZ 06 toilet can be also supplied as AUZ 06N - version with stainless steel flushing cistern which is a part of the toilet. The casing of the toilet is made from the stainless steel of 1,5 mm thickness, the sitting part of 2 mm thickness. AUZ 06 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recomnend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet  
[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUZ 06 is a stainless toilet intended for free-standing on the floor, including grey seat made of hardened durable plastic (white or black seat are possible on order). It is suitable for all places where it is not possible to use wall-hung toilet (e.g. in case of low carrying capacity of the wall). In standard version the outlet is directed into the wall. Outlet directed into the floor is possible on customer's wish. A set with an AUZ 3 automatic flushing system or AUZ 5 automatic flushing system including flushing cistern can be completed. AUZ 06 toilet can be also supplied as AUZ 06N - version with stainless steel flushing cistern which is a part of the toilet. The casing of the toilet is made from the stainless steel of 1,5 mm thickness, the sitting part of 2 mm thickness. AUZ 06 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recomnend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).  
Complete delivery

- 1. Stainless steel closet
- 2. Plastic seat
- 3. Anchoring material

### Requirements for setting up the construction

- 1. Set-up outlet into the floor according to the scheme, d = 110 mm including rubber sleeve for pipe d = 90 mm
- 2. Set-up water inlet

Basic technical information	Water inlet	d = 34 - 50 mm
	Min. water flow	70 l/min
	Outlet	d = 90 mm
	Weight	23 kg

Figures

