

AUP 32 - automatic VISIT urinal with automatic flushing system - 12 V, 50 Hz



AUP 32 (VISIT ceramics produced by Keramag) is a ceramic bowl urinal with automatic flushing device and cover designed especially to bathrooms in both homes and hotels. The AUP 32 automatic bowl urinal is designed for toilettes where user comfort and hygiene are required together with economic use of water. The electronics scans and assesses processes in the trap and upon the result it directs the device to flush. Only one litre is enough to flush the bowl urinal. If somebody approaches the bowl urinal without using it, the control electronics does not react. It prevents needless flushing in the case of incidental short-term entrance (passing by the bowl urinal, etc.). After 24 hours of no activity, the bowl urinal automatically flushes. Its construction enables fast assembly ? simply connecting and hanging the set onto a wall. For easy assembly is important to observe the requirements for setting up the construction as per the scheme. The flushing system is protected against mechanical damage, even wilful, as all components are placed in the body of the ceramics. The urinal AUP 32 is due to its cover not suitable for social facilities.

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUP 32 (VISIT ceramics produced by Keramag) is a ceramic bowl urinal with automatic flushing device and cover designed especially to bathrooms in both homes and hotels. The AUP 32 automatic bowl urinal is designed for toilettes where user comfort and hygiene are required together with economic use of water. The electronics scans and assesses processes in the trap and upon the result it directs the device to flush. Only one litre is enough to flush the bowl urinal. If somebody approaches the bowl urinal without using it, the control electronics does not react. It prevents needless flushing in the case of incidental short-term entrance (passing by the bowl urinal, etc.). After 24 hours of no activity, the bowl urinal automatically flushes. Its construction enables fast assembly ? simply connecting and hanging the set onto a wall. For easy assembly is important to observe the requirements for setting up the construction as per the scheme. The flushing system is protected against mechanical damage, even wilful, as all components are placed in the body of the ceramics. The urinal AUP 32 is due to its cover not suitable for social facilities.

Complete delivery

1. Ceramic VISIT urinal
2. self-priming siphon with sensor and electronics
3. battery holder (AUP 32.B)
4. cylindrical batteries 1,5 V (AUP 32.B) ? 4 pcs.
5. electromagnetic valve
6. corner valve with filter
7. self-priming siphon
8. connecting hoses

Requirements for setting up the construction

1. Set-up water inlet, pipe 1/2" ? as per picture
2. Set-up outlet d = 50 mm
3. Set-up cable for power supply ? 12 V, 50 Hz from source of power supply ZAC

Download information about the product

- [AUP 32 data for projectants - \(100 kB \)](#)

Basic technical information

| | |
|-----------------------------|--|
| Water inlet | G 1/2" |
| Water pressure | 0,2 ? 0,8 MPa (AUP 32.B) |
| | AA batteries ? 1,5 V (AUP 32.B) ? 4 pcs. |
| Outlet | d = 50 mm |
| Adjustable time of flushing | 1 ? 16 s (adjusted to 5 s) |
| Power supply | 12 V, 50 Hz (AUP 32) |
| Power requirement | 6 VA (AUP 5) |
| Power supply unit | ZAC 1/20 (max. 3 x AUP 32) |
| Operating life of batteries | approx. 1,5 year at 100 flushes a day |
| Weight | 10,5 kg |

Figures

