

AUP 33 - ceramic urinal SUBWAY with cover - including automatic flushing system



AUP 33 (SUBWAY ceramics produced by Villeroy - Boch) is a ceramic bowl urinal with automatic flushing device and cover designed especially to bathrooms in both homes and hotels. The APU 32 automatic bowl urinal is designed for toilettes where user comfort and hygiene are required together with economic use of water. The electronics scans and assesses processes in the trap and upon the result it directs the device to flush. Only one litre is enough to flush the bowl urinal. If somebody approaches the bowl urinal without using it, the control electronics does not react. It prevents needless flushing in the case of incidental short-term entrance (passing by the bowl urinal, etc.). After 24 hours of no activity, the bowl urinal automatically flushes. Construction of the flushing system allows easy installation comprising only connection and suspension of the ceramics on prepared wall. As all elements are incorporated in the ceramics, the flushing system is protected against mechanical injury, both incidental and intentional. The bowl urinal does not contain any optical elements; therefore it removes disadvantages of sensor technology such as soiling or damaging of scanning diodes and their poor dark colour sensitivity. Due to the cover use of the bowl urinal is not suitable for public toilettes.

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Bmo](#)

Description AUP 33 (SUBWAY ceramics produced by Villeroy - Boch) is a ceramic bowl urinal with automatic flushing device and cover designed especially to bathrooms in both homes and hotels. The APU 32 automatic bowl urinal is designed for toilettes where user comfort and hygiene are required together with economic use of water. The electronics scans and assesses processes in the trap and upon the result it directs the device to flush. Only one litre is enough to flush the bowl urinal. If somebody approaches the bowl urinal without using it, the control electronics does not react. It prevents needless flushing in the case of incidental short-term entrance (passing by the bowl urinal, etc.). After 24 hours of no activity, the bowl urinal automatically flushes. Construction of the flushing system allows easy installation comprising only connection and suspension of the ceramics on prepared wall. As all elements are incorporated in the ceramics, the flushing system is protected against mechanical injury, both incidental and intentional. The bowl urinal does not contain any optical elements; therefore it removes disadvantages of sensor technology such as soiling or damaging of scanning diodes and their poor dark colour sensitivity. Due to the cover use of the bowl urinal is not suitable for public toilettes.

Complete delivery

1. ceramic urinal SUBWAY (Villeroy - Bosh)
2. electronics with sensor
3. electromagnetic valve
4. corner valve with filter
5. connecting hoses
6. self-priming siphon
7. battery holder (AUP 33.B)
8. AA batteries 1,5 V (AUP 33.B) ? 4 pcs

Requirements for setting up the construction

1. Set-up water inlet, pipe 1/2" ? as per picture

- 2. Set-up outlet d = 50 mm
- 3. Set-up cable for power supply ? 12 V, 50 Hz from source of power supply ZAC (not for AUP 33.B)

Download information about the product

- [AUP 33 data for projectants - \(51 kB \)](#)

Basic technical information	Water inlet	G 1/2"
	Water pressure	0,1 ? 1,0 MPa (AUP 33) ZAC 1/50 (max. 8 x AUP 33)
	Outlet	d = 50 mm
	Time of flushing	1 ? 20 s (adjusted to 5 s)
	Power supply	12 V, 50 Hz (AUP 33)
	Power requirement	6 VA
	Power supply unit	ZAC 1/20 (max. 3 x AUP 33)
	Weight	11 kg

Figures

