

## SPS 02 - solar shower column



SPS 02 is an integral stainless steel shower column using insulation to heat the water. Part of the column is painted black to improve heating effect. The temperature of the outflow water can be regulated by means of spherical valves placed on the front panel of the column. The column is equipped with a shower arm that allows greater multi-purpose connections by means of a hose. The column is suitable for private swimming pools, gardens etc. It is intended to be placed in an open space and there are two ways to anchor the column ? fixing the anchoring construction by means of joggles and screws, or anchoring it by means of strands when, e.g., placed on a lawn. SPS 02 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description SPS 02 is an integral stainless steel shower column using insulation to heat the water. Part of the column is painted black to improve heating effect. The temperature of the outflow water can be regulated by means of spherical valves placed on the front panel of the column. The column is equipped with a shower arm that allows greater multi-purpose connections by means of a hose. The column is suitable for private swimming pools, gardens etc. It is intended to be placed in an open space and there are two ways to anchor the column ? fixing the anchoring construction by means of joggles and screws, or anchoring it by means of strands when, e.g., placed on a lawn. SPS 02 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Complete delivery

1. integral stainless steel shower column
2. shower arm
3. pressure valve ? 2 pcs
4. anchoring construction
5. connecting material

Requirements for setting up the construction


1. when fixing by means of screws into joggles
2. Corresponding consolidated ground (concrete, etc.)

Download information about the product

- [SPS 02 data for projectants - \( 35 kB \)](#)

Basic technical information	Water inlet	G 1/2"
	Capacity of reservoir	28 l
	Water pressure	0,1 ? 1,0 MPa
	Water flow	approx. 6 l/min.
	Dimensions	180 x 130 x 2000 mm
	Weight	20 kg

Figures



Reviews

There are yet no reviews for this product.