


OZ 04 - stainless steel floor channels with 6 mm slit, connectible



OZ 04 is an assembly of floor gully and slot channels with a slot of 6 mm. The floor gully OZ 04.V with braz and 6 mm slot is the basic element of the assembly and is connected by welding to one piece of channel in chosen length. The other side of the gully can be connected by means of screwed sleeves and seal to other channels, creating one long slit (with only a slight interruption between channel and gully) with length up to 5130 mm. Channels are manufactured in two standard lengths ? 1250 mm and 2500 mm. Other lengths are possible on order. The channel is equipped by external braces; liquid flow is not constrained in any way. The channels are not declined toward the gully. The outlet of the gully is in standard version directed down, on order it can be directed to the side. Products are manufactured from AISI 304 stainless steel or from chemically resistant AISI 316 stainless steel. Custom-made channels can be adjusted according to your requirements - for example connection of more pieces in a serie of channels, different lengths, etc. ? as you require.

Rating: Not Rated Yet
[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)


Description OZ 04 is an assembly of floor gully and slot channels with a slot of 6 mm. The floor gully OZ 04.V with braz and 6 mm slot is the basic element of the assembly and is connected by welding to one piece of channel in chosen length. The other side of the gully can be connected by means of screwed sleeves and seal to other channels, creating one long slit (with only a slight interruption between channel and gully) with length up to 5130 mm. Channels are manufactured in two standard lengths ? 1250 mm and 2500 mm. Other lengths are possible on order. The channel is equipped by external braces; liquid flow is not constrained in any way. The channels are not declined toward the gully. The outlet of the gully is in standard version directed down, on order it can be directed to the side. Products are manufactured from AISI 304 stainless steel or from chemically resistant AISI 316 stainless steel. Custom-made channels can be adjusted according to your requirements - for example connection of more pieces in a serie of channels, different lengths, etc. ? as you require.

Requirements for setting up the construction

- 1. Hole prepared for the channel bedding in compliance with technical drawing
- 2. Set up outlet for d = 50 mm

Basic technical information	Floor gully	
	dimensions	46 x 1250 (2500 mm)
	outlet	d = 50 mm
	material	AISI 304
	Chanells	
	width of slit	6 mm

Figures



Reviews

There are yet no reviews for this product.