

AUM 020.TVB - stainless wahsbasin with automatic tap AUM 3, with thermostatic valve



AUM 020 is a new stainless steel round washbasin with round inner sink intended for wall mounting. Standard delivery includes the waste trap connected to the overflow. Round inner corners ensures easy water flowoff from the sink to waste trap as well as easy cleaning. Stainless steel sheathing makes the washbasin durable and increases its resistancy to damage. Standard version does not include the opening for the tap. Opening can be made free of charge. Its diameter and location must be specify with the order. The washbsin can be fitted with the automatic tap AUM 3, supplied with 12 V from power supply ZAC or with 6 V from AA batteries. Version types according to the automatic tap: a) for one pre-mixed water AUM 020.1, AUM 020.1B) b) for hot and cold water with mixing vavle(AUM 020.2,AUM 020.2B) c) for hot and cold water with thermostatic valve (AUM 020.TV, AUM 020.TVB). The washbasin is manufactured from the stainless steel AISI 304. For cleaning we recomnnd WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 8931211).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUM 020 is a new stainless steel round washbasin with round inner sink intended for wall mounting. Standard delivery includes the waste trap connected to the overflow. Round inner corners ensures easy water flowoff from the sink to waste trap as well as easy cleaning. Stainless steel sheathing makes the washbasin durable and increases its resistancy to damage. Standard version does not include the opening for the tap. Opening can be made free of charge. Its diameter and location must be specify with the order. The washbsin can be fitted with the automatic tap AUM 3, supplied with 12 V from power supply ZAC or with 6 V from AA batteries. Version types according to the automatic tap: a) for one pre-mixed water AUM 020.1, AUM 020.1B) b) for hot and cold water with mixing vavle(AUM 020.2,AUM 020.2B) c) for hot and cold water with thermostatic valve (AUM 020.TV, AUM 020.TVB). The washbasin is manufactured from the stainless steel AISI 304. For cleaning we recomnnd WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 8931211).

Complete delivery

1. stainless washbasin
2. small anchoring material
3. waste trap

Requirements for setting up the construction

1. Set-up outlet d = 40 mm according to the scheme
2. Water inlet G 1/2" (only for versions with automatic tap)
3. Power supply 12 V, 50 Hz from source ZAC (only for versions with automatic tap)

Download information about the product

- [AUM 020 data for projectants - \(24 kB \)](#)

Basic technical informationAUM 020

Dimensions

465 x 459 x 278 mm

Inner dimensions of sink	d 390 x 181 mm
Outlet	d = 40 mm
AUM 020.1, .2, .TV (+ battery version .B)	
Water inlet	G 1/2"
Water pressure	1 - 10 Bar (12 V, version), 2 - 8 Bar (6 V version)
Power supply	12 V, 50 Hz
	ZAC 1/50 - max. 8x AUM 020.1, 020.TV, max. 5x AUM 020.2
Power requirement for 12 V versions	6 VA, (10 VA by AUM 020.2)
Source of power supply for 12 V versions	ZAC 1/20 - max. 3x AUM 020.1, 020.TV, max. 2x AUM 020.2

Figures

