

AUM 026 - Sensor-controlled tainless wall-mounted washbasin ? with a soap dispenser and hand dryer



AUM 026 is a stainless steel, partly wall-built in washbasin, containing the combination of a liquid soap dispenser, water tap and hand dryer in a small space. Controlled by durable piezo-pushbuttons, electronically controlled turn-off (the period of water running is settable by the owner). The washbasin is to be mounted through the wall, all technology components are behind the wall, and thus cannot be damaged by users (anti-vandal design). A wall-hanged version may be supplied to order, or a version without any of the functions (e.g. only water plus soap, or water plus dryer). The washbasin is made of AISI 304 stainless steel. A recommended cleaning agent for stainless products maintenance: Würth ? preservation (order no. 0893 121 K), cleaning (order no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUM 026 is a stainless steel, partly wall-built in washbasin, containing the combination of a liquid soap dispenser, water tap and hand dryer in a small space. Controlled by durable piezo-pushbuttons, electronically controlled turn-off (the period of water running is settable by the owner). The washbasin is to be mounted through the wall, all technology components are behind the wall, and thus cannot be damaged by users (anti-vandal design). A wall-hanged version may be supplied to order, or a version without any of the functions (e.g. only water plus soap, or water plus dryer). The washbasin is made of AISI 304 stainless steel. A recommended cleaning agent for stainless products maintenance: Würth ? preservation (order no. 0893 121 K), cleaning (order no. 893 121 1).

Complete delivery

1. Stainless-steel washbasin
2. Electronic hand dryer
3. Electronic soap dispenser
4. Electronic water tap
5. Through-wall frame with bolts
6. Waste with a sink trap
7. 230V / 12V source for the electronics

Requirements for setting up the construction

1. Opening in the wall 490 x 600 mm
2. Prepared el. supply cable 3C x 1,5 s 230 V, 50 Hz according to technical scheme
3. Prepared water inlet and outlet according to technical scheme

Basic technical informationPower supply

IP protection

Dimensions (visible from outside)

230 V, 50 Hz

IP 55

700 x 550 x 144 mm

Required thickness of wall

Outlet

min. 100 mm

d = 40 mm

Figures

