

### AUZ 04 - stainless steel free-standing toilet



AUZ 04 is a stainless steel free-standing toilet in vandal-resistant design. It is convenient for all places where it is not possible to use wall-mounted toilet (e.g. in case of low carrying capacity of the wall). In standard version the outlet is directed into the floor. Outlet directed into the wall is possible on customer's wish. A set can be completed with an AUZ 3 automatic flushing system (event. with BSAZ 01) or with any other suitable flushing system with cistern. Standard delivery does not include the plastic seat. Sitting part is made of 3 mm thick material and the edges are rounded for more comfortable sitting. Due to its resistance against vandalism it is intended particularly for modernization of the prisons, diagnostic establishments and other institutions where security is paramount. AUZ 04 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUZ 04 is a stainless steel free-standing toilet in vandal-resistant design. It is convenient for all places where it is not possible to use wall-mounted toilet (e.g. in case of low carrying capacity of the wall). In standard version the outlet is directed into the floor. Outlet directed into the wall is possible on customer's wish. A set can be completed with an AUZ 3 automatic flushing system (event. with BSAZ 01) or with any other suitable flushing system with cistern. Standard delivery does not include the plastic seat. Sitting part is made of 3 mm thick material and the edges are rounded for more comfortable sitting. Due to its resistance against vandalism it is intended particularly for modernization of the prisons, diagnostic establishments and other institutions where security is paramount. AUZ 04 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Complete delivery

1. stainless steel toilet
2. anchoring material

Requirements for setting up the construction

1. Set-up outlet into the floor according to the scheme d = 110 mm with sealing for the pipe d = 90 mm
2. Set-up water inlet

Download information about the product

- [AUZ 04 data for projectants - \( 19 kB \)](#)

Basic technical information Water inlet

d = 34 - 50 mm

Min. water flow  
Outlet  
Weight

70 lts / min.  
d = 90 mm  
20 kg

Figures

