

## AUL 03 - stainless steel wash troughs



AUL 03 is a stainless steel wash troughs with sensor-controlled outflow arms. Water turns on automatically when the user's hands are placed within the sensor's range and turns off when they have been removed. Water stops running with a certain delay after the hands have been removed from the scanning zone. The trough is produced in a wall-hang version (AUL 03.Z) or fixed on a column (AUL 03.S). The water temperature is set by means of a thermostatic valve. Wash trough can be additionally equipped with soap dispensers and disinfection lotions, paper towel dispensers, waste receptacles and other accessories. The finish of the troughs is either right or left (from front view) in accordance with water inlet and outlet. It is necessary to mention the required version when ordering.

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUL 03 is a stainless steel wash troughs with sensor-controlled outflow arms. Water turns on automatically when the user's hands are placed within the sensor's range and turns off when they have been removed. Water stops running with a certain delay after the hands have been removed from the scanning zone. The trough is produced in a wall-hang version (AUL 03.Z) or fixed on a column (AUL 03.S). The water temperature is set by means of a thermostatic valve. Wash trough can be additionally equipped with soap dispensers and disinfection lotions, paper towel dispensers, waste receptacles and other accessories. The finish of the troughs is either right or left (from front view) in accordance with water inlet and outlet. It is necessary to mention the required version when ordering.

Complete delivery

1. trough with sheathing and rear facing
2. column (only AUL 03S)
3. outflow arms (2 ? 4 pcs as per type of trough)
4. electronics with photocell (2 ? 4 pcs as per type of trough)
5. electromagnetic valves (2 ? 4 pcs as per type of trough)
6. corner valves ? 2 pcs
7. thermostatic valve ? 1 pc
8. connecting hoses
9. fittings
10. siphon

Requirements for setting up the construction

1. Set up water inlet at the height of 400 mm from floor level and approx. 300 mm from a specified end of the trough
2. Set up outlet d = 40 mm in the height f 400 mm from floor level and approx. 150 mm from a specified end of the trough
3. Set up cable for power supply ? 12 V, 50 Hz from source of power supply ZAC in the height of 400 ? 500 mm, approx. 300 mm from end of trough where water inlet is set

Download information about the product

- [AUL 03S.1 data for projectants - \( 96 kB \)](#)

<ul style="list-style-type: none"><li><a href="#">AUL 03S.2 data for projectants - ( 96 kB )</a></li><li><a href="#">AUL 03S.3 data for projectants - ( 96 kB )</a></li><li><a href="#">AUL 03S.4 data for projectants - ( 65 kB )</a></li><li><a href="#">AUL 03Z.1 data for projectants - ( 96 kB )</a></li><li><a href="#">AUL 03Z.2 data for projectants - ( 96 kB )</a></li><li><a href="#">AUL 03Z.3 data for projectants - ( 96 kB )</a></li></ul>	
Basic technical information	Water inlet
	Outlet
	Power supply
	Source of power supply
	AUL 03.1
	Number of taps
	Power requirement
	Weight
	AUL 03.2
	AUL 03.3
	AUL 03.4
	G 1/2?
	d = 40 mm
	12 V, 50 Hz
	ZAC 1/20 (AUL 03.1 až .2)
	ZAC 1/50 (AUL 03.3)
	5
	30 VA
	70 kg (AUL 04Z.3 ? 64 kg)

Figures

