

AUL 04.2 - wash trough, wall mounted without taps 1900x430x200



AUL 04 is a stainless steel wall mounted trough. Its construction enables installation of outflow arms, or sensor-controlled taps. The standard version of the trough is without openings for the taps. Openings can be made on a request. Design type of the troughs can be either right or left (from a front point of view) in accordance with water inlet and outlet.

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUL 04 is a stainless steel wall mounted trough. Its construction enables installation of outflow arms, or sensor-controlled taps. The standard version of the trough is without openings for the taps. Openings can be made on a request. Design type of the troughs can be either right or left (from a front point of view) in accordance with water inlet and outlet.

Complete delivery

1. trough
2. cantilever
3. fittings

Requirements for setting up the construction

1. Set up an outlet according to the type of a siphon (siphon is not part of the delivery)

Download information about the product

- [AUL 04.1 data for projectants - \(95 kB \)](#)
- [AUL 04.2 data for projectants - \(95 kB \)](#)
- [AUL 04.3 data for projectants - \(95 kB \)](#)
- [AUL 04.4 data for projectants - \(61 kB \)](#)

Basic technical information

| | |
|----------------------------|-----------------------|
| Outlet | for outled valve 6/4? |
| Total dimension | L x 430 x 400 mm |
| Inner dimensions of trough | L-5 x 330 x 200 mm |
| AUL 04.1 | |
| Lenght L | 3000 mm |
| Weight | 38 kg |
| AUL 04.2 | |
| AUL 04.3 | |
| AUL 04.4 | |

Figures



