AUL 04.3 - wash trough, wall mounted without taps 2500x430x200



AUL 04 is a stainless steel wall mounted trough. Its construction enables installation of outflow arms, or sensor-controlled taps. The standard version of the trough is without openings for the taps. Openings can be made on a request. Design type of the troughs can be either right or left (from a front point of view) in accordance with water inlet and outlet.

Rating: Not Rated Yet

Ask a question about this product

Manufacturer: AZP Brno

Description AUL 04 is a stainless steel wall mounted trough. Its construction enables installation of outflow arms, or sensor-controlled taps. The standard version of the trough is without openings for the taps. Openings can be made on a request. Design type of the troughs can be either right or left (from a front point of view) in accordance with water inlet and outlet.

Complete delivery

- 1. trough
- 2. cantilever
- 3. fittings

Requirements for setting up the construction

1. Set up an outlet according to the type of a siphon (siphon is not part of the delivery)

Download information about the product

- AUL 04.1 data for projectants (95 kB)
- AUL 04.2 data for projectants (95 kB)
- AUL 04.3 data for projectants (95 kB)
- AUL 04.4 data for projectants (61 kB)

Basic technical informationOutlet

Total dimension Inner dimensions of trough AUL 04.1 Lenght L Weight AUL 04.2 AUL 04.3


3000 mm 38 kg

for outled valve 6/4?

 $L-5 \times 330 \times 200 \text{ mm}$

L × 430 × 400 mm

Figures



AUL 04.4

2 / 2