

AUL 04.4 - wash trough, wall mounted without taps 3000x430x200



AUL 04 is a stainless steel wall mounted trough. Its construction enables installation of outflow arms, or sensor-controlled taps. The standard version of the trough is without openings for the taps. Openings can be made on a request. Design type of the troughs can be either right or left (from a front point of view) in accordance with water inlet and outlet.

Rating: Not Rated Yet
[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUL 04 is a stainless steel wall mounted trough. Its construction enables installation of outflow arms, or sensor-controlled taps. The standard version of the trough is without openings for the taps. Openings can be made on a request. Design type of the troughs can be either right or left (from a front point of view) in accordance with water inlet and outlet.
Complete delivery

- 1. trough
- 2. cantilever
- 3. fittings

Requirements for setting up the construction

- 1. Set up an outlet according to the type of a siphon (siphon is not part of the delivery)

Download information about the product

- [AUL 04.1 data for projectants - \(95 kB \)](#)
- [AUL 04.2 data for projectants - \(95 kB \)](#)
- [AUL 04.3 data for projectants - \(95 kB \)](#)
- [AUL 04.4 data for projectants - \(61 kB \)](#)

Basic technical information	Outlet	for outled valve 6/4?
	Total dimension	L x 430 x 400 mm
	Inner dimensions of trough	L-5 x 330 x 200 mm
	AUL 04.1	
	Lenght L	3000 mm
	Weight	38 kg
	AUL 04.2	
	AUL 04.3	
	AUL 04.4	

Figures



