

AUL 05.1 - wall-hang trough of length 1 250 mm



AUL 05 is a stainless steel wall mounted trough with round inner corners. Its construction enables installation of outflow arms, or sensor-controlled taps. The round inner corners make the maintenance easier because the sediments do not get stuck in the corners. The standard version of the trough is without openings for the taps. Openings can be made on a request. Design type of the troughs can be either right or left (from a front point of view) in accordance with water inlet and outlet.

Rating: Not Rated Yet
[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description AUL 05 is a stainless steel wall mounted trough with round inner corners. Its construction enables installation of outflow arms, or sensor-controlled taps. The round inner corners make the maintenance easier because the sediments do not get stuck in the corners. The standard version of the trough is without openings for the taps. Openings can be made on a request. Design type of the troughs can be either right or left (from a front point of view) in accordance with water inlet and outlet.
Complete delivery

- 1. trough
- 2. cantilever
- 3. fittings

Requirements for setting up the construction

- 1. Set up an outlet according to the type of a siphon (siphon is not part of the delivery)

Download information about the product

- [AUL 05.1 data for projectants - \(61 kB \)](#)
- [AUL 05.2 data for projectants - \(62 kB \)](#)
- [AUL 05.3 data for projectants - \(62 kB \)](#)
- [AUL 05.4 data for projectants - \(62 kB \)](#)

Basic technical information		Outlet	for outled valve 6/4?
		Total dimension	L x 430 x 400 mm
		Inner dimensions of trough	L-5 x 330 x 200 mm
		AUL 05.1	
		Lenght L	3000 mm
		Weight	38 kg
		AUL 05.2	
		AUL 05.3	
		AUL 05.4	

Figures

