## AUL 03Z.L - suspension stainless steel wash-trough with back and medical mixers



AUL 03Z.L is a series of stainless steel wash troughs designed for medical environment. The troughs are deeper and higher than the usual ones to provide the user more space. The troughs are also equipped with mixers completed by medical lever. As for the model the number of mixers can be 1 to 4. In compliance with requirements in medical industry the wash troughs are made of stainless steel with improved resistance to chlorine ? AISI 316L (in contrary to standard stainless steel AISI 304 used for normal troughs). The troughs are ballotini sand-blasted ? decent mat finish. Outlet is positioned on the left or on the right (in front view on the lavatory) ? please specify in the order. AUL 03Z.L is manufactured from the stainless steel AISI 316. For cleaning we recommed WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet Ask a question about this product

Manufacturer: AZP Brno

Description AUL 03Z.L is a series of stainless steel wash troughs designed for medical environment. The troughs are deeper and higher than the usual ones to provide the user more space. The troughs are also equipped with mixers completed by medical lever. As for the model the number of mixers can be 1 to 4. In compliance with requirements in medical industry the wash troughs are made of stainless steel with improved resistance to chlorine ? AISI 316L (in contrary to standard stainless steel AISI 304 used for normal troughs). The troughs are ballotini sand-blasted ? decent mat finish. Outlet is positioned on the left or on the right (in front view on the lavatory) ? please specify in the order. AUL 03Z.L is manufactured from the stainless steel AISI 316. For cleaning we recommed WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Complete delivery

- 1. Stainless steel trough with medical lever mixers
- 2. Outlet d = 50 mm
- 3. Suspension bar + fittings
- 4. Interconnecting water supply to individual mixers

Requirements for setting up the construction

1. Set up outlet d = 50 mm

2. Set up hot and cold water inlets G 1/2" according to technical drawing

Basic technical informationWater outlet

Overall dimensions Inner dimensions of trough Material AUL 03Z.1L Length L AUL 03Z.2L AUL 03Z.3L AUL 03Z.4L d = 50 mm L × 460 × 1030 mm L-60 × 360 × 200 mm AISI 316L

3000 mm

Figures

