ASO 02 - automatic wellington dryer



ASO 02 is a wellington dryer with forced air circulation and electric heating. The unit?s principal construction enables a choice of sizes according to the required number of pairs of shoes to be dried. From 1 up to 4 separate drying units can be placed on the carrying frame and each is designed for five pairs of shoes. Each unit is equipped with its own fan to ensure sufficient air circulation. The air is heated by means of an electric heating body. The drying time is pre-set by means of switch clock. Air outlets are equipped with clacks that are automatically closed after putting shoes on.

Rating: Not Rated Yet

Ask a question about this product

Manufacturer: AZP Brno

Description ASO 02 is a wellington dryer with forced air circulation and electric heating. The unit?s principal construction enables a choice of sizes according to the required number of pairs of shoes to be dried. From 1 up to 4 separate drying units can be placed on the carrying frame and each is designed for five pairs of shoes. Each unit is equipped with its own fan to ensure sufficient air circulation. The air is heated by means of an electric heating body. The drying time is pre-set by means of switch clock. Air outlets are equipped with clacks that are automatically closed after putting shoes on.

Complete delivery

- 1. carrying frame of the dryer
- 2. drying units (1 ? 4 pcs per type of dryer)
- 3. control panel control panel
- 4. fans (1 ? 4 pcs per type of dryer)
- 5. connecting cable with fork

Requirements for setting up the construction

- 1. Set up power supply ? 230 V, 50 Hz ? cable CYKY 3Cx1,5-2,5 protected by circuit breaker of 10 A and ended with f plug.
- 2. Attention! The ASO 02 automatic dryer can be installed only in certain premises according to norm ?SN 32 20 00 ? 3 and ?SN 32 20 00 ? 5 2 51
- 3. Increased protection to IP 54 can be made to order.

Download information about the product

- ASO 02.1 data for projectants (107 kB)
- ASO 02.2 data for projectants (107 kB)
- ASO 02.3 data for projectants (107 kB)
- ASO 02.4 data for projectants (107 kB)

Basic technical informationPower supply

230 V, 50 Hz

Air temperature Time of drying ASO 02.1 Number of pairs Power requirement Weight ASO 02.2 ASO 02.3 ASO 02.4 15 °C above temperature of surrounding min. 15 minutes (setting switch clock)

20 1 280 W 64 kg

Figures

