ASO 03 - dryer for 3 pairs of shoes? with komaxit surface finish



ASO 03 is a dryer with komaxit surface finish designed to dry 3 pairs of shoes. Drying is ensured by forced heated-air flow which prevents hot & humid environment convenient for bacterial multiplication as in systems without the air flow. The delivery includes long revolving arms suitable for boots? e.g. for ski boots, wellingtons, etc. The dryer can be placed in open space on the floor, by the wall (it includes a balancing stand) or can be attached to wall (using a bracket included in the delivery). The dryer is equipped by single-ended cord on one side and by a connector on the opposite side? more dryers can therefore be connected in series. If required the dryer can be equipped by ozone generator to kill disease-producing bacteria. The dryer must be located in a ventilated room to avoid unacceptable concentration of harmful ozone.

Rating: Not Rated Yet

Ask a question about this product

Manufacturer: AZP Brno

Description ASO 03 is a dryer with komaxit surface finish designed to dry 3 pairs of shoes. Drying is ensured by forced heated-air flow which prevents hot & humid environment convenient for bacterial multiplication as in systems without the air flow. The delivery includes long revolving arms suitable for boots? e.g. for ski boots, wellingtons, etc. The dryer can be placed in open space on the floor, by the wall (it includes a balancing stand) or can be attached to wall (using a bracket included in the delivery). The dryer is equipped by single-ended cord on one side and by a connector on the opposite side? more dryers can therefore be connected in series. If required the dryer can be equipped by ozone generator to kill disease-producing bacteria. The dryer must be located in a ventilated room to avoid unacceptable concentration of harmful ozone.

Complete delivery

- 1. Dryer with service cable
- 2. Universal stand to keep balance on the floor, by the wall or to be fixed to wall
- 3. Fittings

Download information about the product


ASO 03 data for projectants - (35 kB)

Basic technical informationElectricity supply
Electric input
Air temperature

230 V, 50 Hz 70 VA

max. 15°C above the surrounding temperature

Figures



Reviews

There are yet no reviews for this product.