

## SA 1 - subsurface shower unit



SA 1 is a subsurface shower unit intended for new buildings or for reconstructions of social facilities. The SA shower unit is intended for usage only in connection with AZP Brno coin-operated controls (version types MAS 1, MAS 2). The shower is equipped with an electromagnetic valve which opens the water inlet. The user operates the shower by means of a press button. We recommend use of SP 1, SP 2, SP 3, SP 4 or SP 5 shower heads in combination with SA 1 shower unit. SA 1 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description SA 1 is a subsurface shower unit intended for new buildings or for reconstructions of social facilities. The SA shower unit is intended for usage only in connection with AZP Brno coin-operated controls (version types MAS 1, MAS 2). The shower is equipped with an electromagnetic valve which opens the water inlet. The user operates the shower by means of a press button. We recommend use of SP 1, SP 2, SP 3, SP 4 or SP 5 shower heads in combination with SA 1 shower unit. SA 1 is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Complete delivery

1. installation box
2. inlet and outlet bolting
3. stainless steel casing
4. control button
5. electromagnetic valve (SA 1.TV)
6. spherical valve (SA 1.1)
7. covering metal assembly plate (SA 1.1)
8. mounting spacer tray
9. inner connecting hoses (SA 1.TV)
10. small assembly materials

Requirements for setting up the construction

1. Set up alcove for installation of casing of the valve ? size is determined according to used type of SA 1 armature  
SA 1.1: 150 x 150 x 70 mm  
SA 1.TV: 290 x 170 x 70 mm
2. Set up water inlet
3. Set up cable for power supply to be connected with MAS
4. Other setting for total configuration ? see product datasheet of coin-operated controls MAS 1 or MAS 2

Basic technical information  
Water inlet  
Outlet to shower arm

G 1/2"

G 1/2"

Water pressure	1 - 10 bar (0,1 ? 1,0 MPa)
Power supply	12 V, 50 Hz
Power requirement	5 VA
Source of power supply	MAS 1 or MAS 2
Weight	SA 1.1 ? 1,1 kg SA 1.TV ? 3,5 kg

## Figures

