

MSE2 N.6E - st.steel column with 6 protected sockets



MSE 2N are stainless steel columns for unpaid electricity release. Standard version types offer 2, 4 or 6 el. sockets including overcurrent and short-circuit protection as well as protective switch. Looping of el.cables is possible inside the column, therefore it is not necessary to connect every column by individual el.cable from central switchbord. Each column is equipped with small roof protecting the stand against direct rain and with opening in its lower part for ventilation. On order it can be also equipped with light. MSE 2N are manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recomnend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description MSE 2N are stainless steel columns for unpaid electricity release. Standard version types offer 2, 4 or 6 el. sockets including overcurrent and short-circuit protection as well as protective switch. Looping of el.cables is possible inside the column, therefore it is not necessary to connect every column by individual el.cable from central switchbord. Each column is equipped with small roof protecting the stand against direct rain and with opening in its lower part for ventilation. On order it can be also equipped with light. MSE 2N are manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recomnend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Complete delivery

1. stainless steel column
2. protective switch and short-circuit protection for each socket
3. el. sockets and el. connection
4. lock
5. anchoring construction

Requirements for setting up the construction

1. Set-up concrete base for installation of anchoring bolts
2. Set-up supply cable to the middle (? 50 mm) of the column base

Basic technical information	Max.outer dimensions	440 x 300 x 970 mm
	Input voltage	3x 400 V, 50 Hz, TN-S
	Max.cross section of el.cable	5x 25 mm ²
	Looping of supply cables	yes
	Output voltage	230 V
	Output current	10 A

Figures

