

## BSNZ 01 - Safety stainless steel toilet



BSNZ 01 is a stainless steel wall-hung closet with satin finish. Assembly inlets are the same as for any commonly used ceramic closet. A set with AUZ 3 automatic flushing system and KZ 1 cantilever or with AUZ 5 (in-wall toilet module) flushing system can be completed. The AUZ 3 and AUZ 5 flushing systems and KZ1 cantilever have to be ordered separately. Automatic flushing system uses photocell sensor for contactless control. After leaving the scanning zone, the flushing system is activated. AUZ 3 flushing system brings maximum water savings. Because of its high resistance to damage, BSNZ 01 is intended particularly for modernization of the prisons, diagnostic establishments and other institutions where security is paramount.

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description BSNZ 01 is a stainless steel wall-hung closet with satin finish. Assembly inlets are the same as for any commonly used ceramic closet. A set with AUZ 3 automatic flushing system and KZ 1 cantilever or with AUZ 5 (in-wall toilet module) flushing system can be completed. The AUZ 3 and AUZ 5 flushing systems and KZ1 cantilever have to be ordered separately. Automatic flushing system uses photocell sensor for contactless control. After leaving the scanning zone, the flushing system is activated. AUZ 3 flushing system brings maximum water savings. Because of its high resistance to damage, BSNZ 01 is intended particularly for modernization of the prisons, diagnostic establishments and other institutions where security is paramount.

Complete delivery

1. stainless steel closet
2. anchoring material

Requirements for setting up the construction

1. Water installation set up as per picture
2. Set-up alcove for installation casket (only for AUZ 3)
3. Set-up cable for power supply ? 12 V, 50 Hz from source of power supply ZAC (only for AUZ 3)
4. Set-up outlet d = 90 mm as per picture
5. Set-up the cantilever or other system for hanging the closet

Download information about the product

- [BSNZ 01 data for projectants - \( 42 kB \)](#)

Basic technical information	Water inlet	d = 34 mm
	Minimum water flow capacity	70 l/min.
	Outlet	d = 90 mm
	Required spacing between bolts	180 mm
	Weight	11 kg

#### Reviews

There are yet no reviews for this product.