

BSNZ 02 INV - vandal-proof stainless steel free-standing toilet for handicapped people



BSNZ 02 INV is a vandal-proof stainless steel toilet without automatics which is intended for free-standing. The closet is based on standard BSNZ 02 which is elevated and protracted to comply with the ordinance for products for disabled people. It is convenient in all places where it is not possible to use wall-hung toilet (e.g. in case of low carrying capacity of the wall). In standard version the outlet is directed into the floor. Outlet directed into the wall is possible on customer's wish. The housing of the toilet is made from the stainless steel of 2 mm thickness, the sitting part of 4 mm thickness. For higher comfort of the user are the edges of the sitting part grinded down. The closet is also produced in standard version (AUZ 02 INV) which is made from the stainless steel sheet of 1,5 mm thickness, sitting part of 2 mm thickness and is quipped with plastic sitting board. BSNZ 02 INV is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommned WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description BSNZ 02 INV is a vandal-proof stainless steel toilet without automatics which is intended for free-standing. The closet is based on standard BSNZ 02 which is elevated and protracted to comply with the ordinance for products for disabled people. It is convenient in all places where it is not possible to use wall-hung toilet (e.g. in case of low carrying capacity of the wall). In standard version the outlet is directed into the floor. Outlet directed into the wall is possible on customer's wish. The housing of the toilet is made from the stainless steel of 2 mm thickness, the sitting part of 4 mm thickness. For higher comfort of the user are the edges of the sitting part grinded down. The closet is also produced in standard version (AUZ 02 INV) which is made from the stainless steel sheet of 1,5 mm thickness, sitting part of 2 mm thickness and is quipped with plastic sitting board. BSNZ 02 INV is manufactured from the stainless steel AISI 304. Other materials (e.g. AISI 316) possible on order. For cleaning we recommned WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Complete delivery

1. Stainless steel closet
2. Fixing material

Requirements for setting up the construction

1. Set-up outlet d = 110 mm according to the scheme with the rubber sleeve for the pipe d = 90 mm
2. Water installation set up as per picture d = 34 - 50 mm according to chosen sealing

Download information about the product

- [BSNZ 02 INV data for projectants - \(29 kB \)](#)

Basic technical information	Water inlet	d = 34 ?50 mm
	Min. required water flow	70 liter?/min
	Outlet	d = 90 mm
	Weight	26 kg

Figures

