

BSAS 03 - vandal-resistant wall mounted shower



BSAS 03 is a safety wall mounted shower for one pre-mixed water. The shower is made of 2 mm thick stainless sheet and equipped by anti-vandal economic shower arm with the flow rate of 7 litres / minute. Water is opened by pressing the anti-vandal stainless button. Time period of water running after the button is pressed can be set by the operator. Within the electronic a forced timeout can be set ? i.e. the time when the button does not react ? to prevent intentional wasting of water. The button reacts on the trailing edge, i.e. not at pressing but only at releasing, to avoid forced caging of the button and subsequent continuous flow of water. BSAS 03 is manufactured from the stainless steel AISI 304. For cleaning we recommned WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer: [AZP Brno](#)

Description BSAS 03 is a safety wall mounted shower for one pre-mixed water. The shower is made of 2 mm thick stainless sheet and equipped by anti-vandal economic shower arm with the flow rate of 7 litres / minute. Water is opened by pressing the anti-vandal stainless button. Time period of water running after the button is pressed can be set by the operator. Within the electronic a forced timeout can be set ? i.e. the time when the button does not react ? to prevent intentional wasting of water. The button reacts on the trailing edge, i.e. not at pressing but only at releasing, to avoid forced caging of the button and subsequent continuous flow of water. BSAS 03 is manufactured from the stainless steel AISI 304. For cleaning we recommned WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 893 121 1).

Complete delivery

1. st. steel shower panel with economic shower arm SP2
2. electronics including the electromagnetic valve
3. vandal-proof button with detecting element
4. connecting hoses and assembly material

Requirements for setting up the construction

1. set-up water supply pipe G 1/2"
2. el. cable for power supply (12 V from power supply ZAC)

Basic technical information	Power supply	12 V, 50 Hz
	Power requirement	max. 6 VA
	Water pressure	0,1?1 Mpa (1-10 Bar)
	Adjustable time of showering	1 s ? 250 s po 1 s

Figures

