

AUM 021.2B - stainless wahsbasin with automatic tap AUM 3, for hot and cold water



AUM 021 is a stainless steel washbasin with simple design and interesting price. Round inner corners ensure easy water flowoff from the sink. Delivery includes waste trap and all fixing material. Due to its resistancy to damage, it is intended for replacing ceramic washbasins in areas where higher endurance of material is required. Standard version does not include the opening for the tap. Opening can be made free of charge. Its diameter and location must be specify with the order. The washbsin can be fitted with the automatic tap AUM 3, supplied with 12 V from power supply ZAC or with 6 V from AA batteries. In standard version the washbasin has a brushed surface finish (possible sandblasted matt finish on order). The washbasin is manufactured from the stainless steel AISI 304. For cleaning we recommned WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 8931211).

Rating: Not Rated Yet
[Ask a question about this product](#)
Manufacturer: [AZP Brno](#)

Description AUM 021 is a stainless steel washbasin with simple design and interesting price. Round inner corners ensure easy water flowoff from the sink. Delivery includes waste trap and all fixing material. Due to its resistancy to damage, it is intended for replacing ceramic washbasins in areas where higher endurance of material is required. Standard version does not include the opening for the tap. Opening can be made free of charge. Its diameter and location must be specify with the order. The washbsin can be fitted with the automatic tap AUM 3, supplied with 12 V from power supply ZAC or with 6 V from AA batteries. In standard version the washbasin has a brushed surface finish (possible sandblasted matt finish on order). The washbasin is manufactured from the stainless steel AISI 304. For cleaning we recommned WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 8931211).
Complete delivery

- 1. stainless washbasin
- 2. small anchoring material
- 3. waste trap

Requirements for setting up the construction

- 1. Set-up outlet d = 40 mm according to the scheme
- 2. Water inlet G 1/2" (only for versions with automatic tap)
- 3. Power supply 12 V, 50 Hz from source ZAC (only for versions with automatic tap)

Download information about the product

- [AUM 021 data for projectants - \(27 kB \)](#)

Basic technical informationAUM 021

Dimensions	470 x 410 x 177 mm
Inner dimensions of sink	358 x 335 x 150 mm
Outlet	d = 40 mm
AUM 021.1, .2, .TV (+ battery version .B)	
Water inlet	G 1/2"

Water pressure	1 - 10 Bar (12 V, version), 2 - 8 Bar (6 V version)
Power supply	12 V, 50 Hz
	ZAC 1/50 - max. 8x AUM 021.1, 021.TV, max. 5x AUM 021.2
Power requirement for 12 V versions	6 VA, (10 VA by AUM 021.2)
Source of power supply for 12 V versions	ZAC 1/20 - max. 3x AUM 021.1, 021.TV, max. 2x AUM 021.2

Figures

