

AUM 022 Z.TV -Rozsdamentes acél mosdó, termosztatikus szeleppel - 12 V, 50 Hz



AUM 022 is a small stainless steel washbasin intended to be mounted on the wall. Due to its small size, this washbasin is suitable especially for areas with less space where the requirements for hygiene are required. The washbasin is produced in two standard version types: with fixing consoles (AUM 022N) and more durable version with stainless sheathing (AUM 022Z). Surface finish is standardly brushed, but sandblasted matt finish is possible on order. The washbasin can be delivered either without an automatic tap, only with opening of diameter of 29 mm for the tap or fitted with our popular automatic tap AUM 3 in all version types - for one water, for hot and cold water or with thermostatic valve. All version types can be supplied with 12 V, 50 Hz (from source ZAC) or with 6 V (from AA batteries). The washbasin is manufactured from the stainless steel AISI 304. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 8931211).

Értékelés: Még nincs értékelés

[Tegye fel kérdését a termék?](#)

Gyártó: [AZP Brno](#)

Leírás

AUM 022 is a small stainless steel washbasin intended to be mounted on the wall. Due to its small size, this washbasin is suitable especially for areas with less space where the requirements for hygiene are required. The washbasin is produced in two standard version types: with fixing consoles (AUM 022N) and more durable version with stainless sheathing (AUM 022Z). Surface finish is standardly brushed, but sandblasted matt finish is possible on order. The washbasin can be delivered either without an automatic tap, only with opening of diameter of 29 mm for the tap or fitted with our popular automatic tap AUM 3 in all version types - for one water, for hot and cold water or with thermostatic valve. All version types can be supplied with 12 V, 50 Hz (from source ZAC) or with 6 V (from AA batteries). The washbasin is manufactured from the stainless steel AISI 304. For cleaning we recommend WÜRTH detergents ? material preservation (no. 0893 121 K) and material cleaning (no. 8931211).

Szállított termékek

1. stainless washbasin with consoles (AUM 022 N)
2. stainless washbasin with sheathing (AUM 022 Z)
3. waste trap
4. small anchoring material
5. automatic tap (only with version with automatic tap)

A Beüzemeléshez szükséges

1. Set-up water inlet G 1/2"
2. Set-up electric cable for 12 V from source ZAC (only by 12 V version)


3. Set-up outlet d = 40 mm

További információk a termékről

- [AUM 022 N \(všechny verze\) data for projectants - \(30 kB \)](#)
- [AUM 022 Z \(všechny verze\) data for projectants - \(29 kB \)](#)


Alapvető műszaki adatok	Érzékelési tartomány	adjusted automatically
	Víz becsatlakozás	G 1/2"
	Kivezetés	d = 40 mm
	Méret	400 x 295 x 180 mm AUM 022N
	Inner dimensions of sink	2 - 8 Bar (by 6 V verzió)
	Adjustable time of after flow	346 x 248 x 103 mm
	IP védettség	0÷4 s (alapbeállítás 1 sec)
	Tápegység	IP 55
	Felhasználható energiaforrások	12 V, 50 Hz (AUM 022 N.1, .2. TV; AUM 022 Z.1, .2, .TV)
		ZAC 1/20 - max. 3× AUM 022 N.1, Z.1 N.TV, Z.TV; max.
		2x AUM 022 N.2, Z.2)
	Víz nyomás	1 - 10 Bar (by 12 V verzió)
	Súly	4 kg

ÁbrákAUM 022 N



D -
AUM 022 Z

outlet



D -

outlet

Vélemények

Még senki sem nyilvánított véleményt erről a termékről.